Giulia

DISPLAY CONCEPTS

Refrigerated Showcase



Structure: stainless steel

Display surface: stainless steel or steel with food-

approved black plastic coating

Front glass: straight tempered extra-clear glass

panels opened via Hydro-lift pistons **Glass panels**: tempered and heated

Front & side base panels: thermoformed ABS side

panel with inserts in various colors

Ventilation: fan-assisted refrigeration with thermostat valve and choice of fan settings

Compressor: internal or remote

Defrosting: automatic with electronic control

Lighting: high luminosity LED **Electric:** 220V 20A 1Phase

Plumbing: condensate drain with remote

compressor

info@fmdisplayconcepts.com

800-889-3975

www.fmdisplayconcepts.com

Features: Giulia is a multi-purpose, multifunction professional showcase. Designed for pastries, bread and fresh foods, it has a complete range of straight and corner static or fan assisted refrigerated, hot, ambient or chocolate modules, which can all be installed in-line with unbroken surfaces. It is available with total black or total white finishes or customized to requirements in a vast range of optional finishes, colors and woods.

Static or forced air refrigeration of the display surface, depending on load requirements and the type of product for display. The insulated supporting structure and the rear ventilation grilles are in AISI 304 stainless steel and CFC-free expanded polyurethane. Giulia can be equipped with the optional "Frigoconnect" HACCP cloud and remote control wi-fi system.

The rugged supporting structure has black or silver corrosion-proof anodized aluminum profiles and shelves, with LED lights fitted in both the top and the vertical uprights to ensure perfect lighting on all display surfaces, which may be in AISI 304 stainless steel, or in steel with food-approved black plastic coating (as customer prefers).







Giulia

Refrigerated Showcase

VETRINA PASTICCERIA STATICA STATIC PASTRY SHOWCASE VITRINE A PATISSERIE À FROID STATIQUE VITRINE KONDITOREIWAREN STATISCH




VENTILATED PASTRY SHOWCASE VITRINE A PATISSERIE À FROID VENTILÉE VITRINE KONDITOREIWAREN UMLUFT



VETRINA PASTICCERIA NEUTRA NON-REFRIGERATED PASTRY SHOWCASE

VITRINE NON RÉFRIGÉRÉE PATISSERIE VITRINE KONDITOREIWAREN NEUTRAL



Feature	inches	mm	HP Internal	Watt Int.	Circ. Amp
Depth (All)	44.5	1125			
Height (120)	47.2	1200			
Height (137)	53.9	1370			
Length (L-1150)	46.9	1190	3/8	822	20
Length (L-1500)	60.6	1540	1/2	1052	20
Length (L-1650)	66.5	1690	1/2	1052	20
Length (L-1850)	74.4	1890	1/2 M	1261	20
Length (L-2150)	86.2	2190	3/4	1437	20

Operating temperature 32°F/+41°F (+5°/-1°C) **Climate Class 4** (30° C- 55% R.H.) Relative Humidity 55% -60%



 $C \in$

